



PTM SERIES LED POST TOP

- ✓ Wet Location Rated
- ✓ 50,000 Hour Design Life
- ✓ 5 Year Manufacturers Limited Warranty
- ✓ Easy Install On Any Existing Post Top Fixture
- ✓ UL, Energy Star, FCC, CE, and DLC Certified

Nominal Specifications

LifeLux™ STD Rating

Power

50W, 70W, 100W

Voltage

120-277V

Lumen Output

150 Lm/W

Color Temperature

3000K, 3500K, 4000K, 5000K

Design Life

50,000 hrs

CRI

>85

Power Factor

>0.90

Dimensions (D/L/H)

E26 = 3.35" x 7.01" x 9.21"

E27 = 3.35" x 7.01" x 9.29"

E39 = 3.35" x 7.01" x 9.37"

E40 = 3.35" x 7.01" x 9.52"

Certifications

UL, Energy Star, FCC, CE, DLC

Weather Rating

Wet location rated

Warranty

5 Year Limited Manufacturers Warranty

ORDERING DATA: Per chart below

Example : USALED-PTM-50-D2-E26-40K

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
Series	Model	Wattage	Dimmable	Base	Color Temperature
USALED	PTM	50 = 50W 70 = 70W 100 = 100W	D1 = No D2 = Yes	E26 = E26 E27 = E27 E39 = E39 E40 = E40	30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K

Model #	Wattage	CCT	Nominal Lumen Output
USALED-PTM-50	50W	3000K, 3500K, 4000K, 5000K	7,500Lm
USALED-PTM-70	70W	3000K, 3500K, 4000K, 5000K	10,500Lm
USALED-PTM-100	100W	3000K, 3500K, 4000K, 5000K	15,000Lm

Applications

Outdoor Areas

Note : Suitable for Dry and Damp Locations

